

(51) A 47 L - 13/142 (11) EP 1 030 586 A 1

(21) 98966236.6 (25) En (26) En

(22) 13.11.1998 (43) 30.08.2000

(86) 13.11.1998 PCT/EP98/07264

(87) 03.06.1999 WO 99/26523

(30) 14.11.1997 US 971001

(84) BE, DE, DK, ES, FR, GB, IT, NL, SE

(54) AUSWRINGVERFAHREN UND AUSWRINGEINRICHTUNG FÜR
FUSSBODENWISCHGERÄT

◇ WRINGING METHOD AND WRINGING MECHANISM FOR
FLOOR MOP

◇ PROCEDE ET MECANISME D'ESSORAGE POUR BALAI A
FRANGES

(71) Thomasson, Ola, Uardavägen F, 235, 22471 Lund, SE

(74) Moldenhauer, Herbert, Freudenberg Technische Dienste KGHöh-
nerweg 2-4, 69465 Weinheim, DE

(72) Thomasson, Ola, Uardavägen F, 235, 22471 Lund, SE

(57) A floor mop having a stick (10), a mop head (11) including a mop fabric (12) and a lower handle (13) and an upper handle (19). The lower handle is axially and rotatably movable relative to the stick (10) and is attached to one end of the mop fabric (12) of the mop head. The other end of the mop fabric is non-rotatably attached to a lower end of the stick (10). The upper handle (19) is attached to the stick (10) or to an attachment member (16) that is mounted on the stick (10) to enable the rotation of the stick relative to the lower handle (13) to wring the mop fabric (12) of the mop head.

